



RADIOR DIN 6

Designed for cooling systems of automotive engines and stationary engines and for refrigerant systems.

Hose construction

Tube: Black, smooth, heat resistant EPDM rubber compound according to DIN 73411 - 1996*

Reinforcement: Synthetic textile fabrics yarns

Cover: Black, smooth, wrapped finish, heat, ageing and weather-resistant EPDM rubber compound according to DIN 73411 - 1996*

Temperature Range

-40 °C (-40 °F) to +125 °C (+257 °F)

Tolerances:

I.D. ≤ 25 mm - according UNI EN ISO 1307

I.D. > 25 mm - according RMA steel mandrel



- Compounds according to DIN 73411 for: tensile, strength, density, hardness, laceration, swellings, aging and dry residue
- Specific for cooling system at high temperature
- Burst Pressure Value 3:1

According to

UNI EN ISO 1307

Number	ID mm	OD mm	WP bar	BP bar	Weight kg	R min mm
IH30836101/40	10	17	6.0	18	0.17	-
IH30836103/40	13	20	6.0	18	0.21	-
IH30836104/40	15	22	6.0	18	0.23	-
IH30836105/40	16	23	6.0	18	0.25	-
IH30836106/40	18	25	6.0	18	0.27	-
IH30836107/40	20	27	6.0	18	0.30	-
IH30836108/40	22	29	6.0	18	0.33	-
IH30836109/40	25	34	6.0	18	0.48	-
IH36836110/40	28	36	6.0	18	0.52	-
IH36836111/40	30	38	6.0	18	0.55	-
IH36836112/40	32	40	6.0	18	0.58	-
IH36836113/40	35	43	6.0	18	0.63	-
IH36836114/40	38	48	6.0	18	0.88	-
IH36836115/40	40	50	6.0	18	0.92	-
IH36836116/40	42	52	6.0	18	0.96	-
IH36836117/40	45	55	6.0	18	1.02	-
IH36836119/40	50	60	6.0	18	1.11	-

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses