

SEVEN 200

Asphalt and tar hose, wire reinforced, ozone and abrasion resistant, according to EN 13482:2001.

Hose construction

Tube: black, smooth, synthetic rubber.

Reinforcement: plies of steel wire cord plus helix wire.

Cover: black, smooth (wrapped finish), synthetic rubber, weathering, ozone, abrasion, asphalt, and oil resistant.

Temperature range

-15°C to +200°C



- Hose for asphalt and tar hose
- Working pressure 15 bar

Number	ID	OD	WP	Burst pressure	Weight	Bending radius	Max length
	mm	mm	bar	bar	kg/m	mm	m
HB50	51	69,5	15	90	3,26	280	60
1315358	63,5	82	15	90	4,04	345	60
HB75	76	95,5	15	90	5,28	456	60
HB100	102	126,5	15	90	8,41	606	60

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses