



## TBE

Designed for particular applications in fuel systems where textile cover is requested. Suitable for leaded and unleaded fuels and diesel.

### Hose construction

**Tube:** Black, oil and fuel resistant, smooth NBR rubber compound

**Cover:** High tensile polyester textile overbraid, resistant to abrasion, fuel, oil and weathering.

### Temperature Range

-20°C ÷ +90°C

### Tolerances

**I.D.** +0 / -0.5mm

**L** ± 1%



- Available in reels only
- Suitable for B20 and E100 up to 70 °C
- Designed for motorbike fuel supply
- Burst Pressure Value 3:1

Number	ID mm	OD mm	WP bar	BP bar	Weight kg	R min mm
IH11001300/15	3	7	10	30	0.04	30
IH11001345/15	7.5	14.5	10	30	0.13	65

## Contact us:

"DAIS GLOBAL " LTD  
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria  
 Telephone: +359 2 973 27 67  
 Fax: +359 2 973 26 65  
 E-mail: office@daisglobal.eu

## Catalogues:

Ducting hoses  
 Industrial hoses  
 Fittings  
 Safety couplings  
 Chemical resistance table ducting hoses  
 Chemical resistance table hoses