



## TIMBERDUC® PUR 531 SE




Special suction and blast hose in flame-retardant polyurethane resistant to aggressive wood types and wood preservatives, especially suitable:

- for the suction of wood dust and wood chips on wood processing machines
- for abrasive solids such as dust, powder, fibres and chips
- for de-dusting and suction plants
- for CNC machines

### Hose construction

1. spring steel wire integrated in wall
2. extruded tape wall: premium polyurethane, resistant to aggressive wood types and wood preservatives, with flame-retardant additive (Pre-PUR®)
3. wall thickness 0.4 mm approx.



- super-light model
- highly flexible + compressible 3:1
- abrasion-proof
- high tensile strength and tear resistant
- microbe and hydrolysis resistant

### According to

- German TRBS 2153 (formerly BGR 132): capable of electro-static discharge by grounding the spiral

### Temperature range

-40°C ÷ +90°C, with peaks up to +125°C

No	I.D. mm	O.D. mm	Vacuum bar	Bend radius mm	Weight kg/m	Max length m
531-0050-0000	50	58	0,240	58	0,240	5 10
531-0060-0000	60	68	0,190	68	0,340	5 10
531-0063-0000	63	71	0,180	71	0,350	-
531-0065-0000	65	73	0,170	73	0,360	5 10
531-0070-0000	70	78	0,140	78	0,390	5 10
531-0075-0000	75	83	0,130	83	0,410	5 10
531-0080-0000	80	88	0,120	88	0,440	5 10
531-0090-0000	90	98	0,105	98	0,490	5 10
531-0100-0000	100	108	0,080	108	0,520	5 10
531-0102-0000	102	110	0,080	110	0,530	-
531-0110-0000	110	118	0,075	118	0,570	5 10
531-0115-0000	115	123	0,070	123	0,590	-
531-0120-0000	120	128	0,070	128	0,620	5 10
531-0125-0000	125	133	0,055	133	0,640	5 10
531-0127-0000	127	135	0,055	135	0,655	-
531-0130-0000	130	138	0,055	138	0,680	-
531-0140-0000	140	148	0,050	148	0,720	5 10
531-0150-0000	150	158	0,050	158	0,770	5 10

### Contact us:

"DAIS GLOBAL " LTD  
 3, Poruchik Nedelcho Bonchev Str., fl. 5  
 1528 Sofia, Bulgaria  
 Telephone: +359 2 973 27 67  
 Fax: +359 2 973 26 65  
 E-mail: office@daisglobal.eu

### Catalogues:

Ducting hoses  
 Industrial hoses  
 Fittings  
 Safety couplings  
 Chemical resistance table ducting hoses  
 Chemical resistance table hoses



No	I.D. mm	O.D. mm	Vacuum bar	Bend radius mm	Weight kg/m	Max length m
<b>531-0152-0000</b>	152	160	0,050	160	0,780	-
<b>531-0160-0000</b>	160	168	0,045	168	0,820	<b>5 10</b>
<b>531-0170-0000</b>	170	178	0,040	178	0,870	-
<b>531-0175-0000</b>	175	183	0,040	183	0,900	-
<b>531-0180-0000</b>	180	188	0,035	188	0,920	<b>5 10</b>
<b>531-0200-0000</b>	200	208	0,035	208	1,040	<b>5 10</b>
<b>531-0203-0000</b>	203	211	0,035	211	1,060	-
<b>531-0225-0000</b>	225	233	0,025	233	1,170	-
<b>531-0250-0000</b>	250	258	0,015	258	1,300	<b>5 10</b>
<b>531-0254-0000</b>	254	262	0,015	262	1,310	-

## Contact us:

"DAIS GLOBAL " LTD  
 3, Poruchik Nedelcho Bonchev Str., fl. 5  
 1528 Sofia, Bulgaria  
 Telephone: +359 2 973 27 67  
 Fax: +359 2 973 26 65  
 E-mail: office@daisglobal.eu

## Catalogues:

Ducting hoses  
 Industrial hoses  
 Fittings  
 Safety couplings  
 Chemical resistance table ducting hoses  
 Chemical resistance table hoses