

## TORONTO

Hardwall hose for suction and discharge of water and non corrosive fluids. Suitable for agricultural, industrial and other applications.

### Hose construction

**Tube:** black, smooth, synthetic rubber.

**Reinforcement:** high strength synthetic cord and helix wire.

**Cover:** black, smooth, (wrapped finish) synthetic rubber, weathering and ozone resistant.

### Temperature range

-30°C to +70°C



- Hose for suction and discharge of water and non corrosive fluids, weathering and ozone resistant.
- Working pressure 10bar
- Vacuum 0,9bar

Number	ID mm	OD mm	WP bar	Burst pressure bar	Weight kg/m	Bending radius mm	Vacuum bar	Max lenght m
IH36214050	25	33	10	30	0,50	125	0,9	120
IH36214051	30	38	10	30	0,58	150	0,9	120
IH36214052	32	40	10	30	0,63	160	0,9	120
IH36214054	38	47,5	10	30	0,83	190	0,9	120
IH36214055	40	49,5	10	30	0,86	200	0,9	120
IH36214058	51	60,5	10	30	1,12	255	0,9	120
IH36214060	63,5	75	10	30	1,80	380	0,9	120
IH36214064	76	87	10	30	2,06	455	0,9	120
IH36214066	80	91,5	10	30	2,27	480	0,9	120
IH36214067	90	103	10	30	3,50	540	0,9	120
IH36214068	102	114	10	30	3,22	610	0,9	120
IH36214071	120	136	10	30	4,99	660	0,9	60
IH36211010	127	143	10	30	5,15	700	0,9	60
IH36211050	152	170,5	10	30	7,27	1000	0,9	60
IH36211032	203	225	10	30	12,08	1400	0,9	60

### Contact us:

"DAIS GLOBAL " LTD  
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria  
 Telephone: +359 2 973 27 67  
 Fax: +359 2 973 26 65  
 E-mail: office@daisglobal.eu

### Catalogues:

Ducting hoses  
 Industrial hoses  
 Fittings  
 Safety couplings  
 Chemical resistance table ducting hoses  
 Chemical resistance table hoses