



UTD

Suction and discharge hose for IBC's and barrels, rail tankers, tankers and fixed installations. The strong steel helix ensures that the hose maintains its shape during suction and gravity operations.

Hose construction

Tube: Ultra high molecular polyethylene UPE, white, with conductive OHM spiral stripe, smooth bore, abrasion resistant, no discoloration, conductive (Ω /T)

Reinforcement: Thermoplast braids. Type UTS additionally with galvanised steel helix

Cover: EPDM (EPT), black, conductive, zone resistant, UV resistant, flame resistant

Temperature range

- 30° to + 100°C

Steaming out for cleaning and sterilisation permissible up to 130°



Blue-white-blue universal tank hoses for almost all liquid and pasty chemical and petroleum based products and solvents.

According to

EN 12115 and German safety standard TRbF 131.

Number	I.D. mm	O.D. mm	WP bar	BP bar	Weight kg	R min mm
UTD13/40	13	22	16	25	0,3	100
UTD19/40	19	31	16	25	0,5	125
UTD25/40	25	37	16	25	0,6	150
UTD32/40	32	44	16	25	0,9	175
UTD38/40	38	51	16	25	1,0	225

Contact us:

"DAIS GLOBAL " LTD
3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
Industrial hoses
Fittings
Safety couplings
Chemical resistance table ducting hoses
Chemical resistance table hoses