



UTS

Suction and discharge hose for IBC's and barrels, rail tankers, tankers and fixed installations. The strong steel helix ensures that the hose maintains its shape during suction and gravity operations.

Hose construction

Tube: Ultra high molecular polyethylene UPE, white, with conductive OHM spiral stripe, smooth bore, abrasion resistant, no discoloration, conductive (Ω /T)

Reinforcement: Thermoplast braids. Type UTS additionally with galvanised steel helix

Cover: EPDM (EPT), black, conductive, zone resistant, UV resistant, flame resistant

Temperature range

- 30° to + 100°C

Steaming out for cleaning and sterilisation permissible up to 130°



Blue-white-blue universal tank hoses for almost all liquid and pasty chemical and petroleum based products and solvents.

According to

EN 12115 and German safety standard TRbF 131.

Number	I.D. mm	O.D. mm	WP bar	BP bar	Weight kg	R min mm
UTS19/40	19	31	16	25	0,6	90
UTS25/40	25	37	16	25	0,8	100
UTS32/40	32	44	16	25	1,0	125
UTS38/40	38	51	16	25	1,2	150
UTS50/40	50	66	16	25	1,8	200
UTS63/40	63	79	16	25	2,3	250
UTS75/40	75	91	16	25	2,6	300
UTS100/40	100	116	16	25	4,2	400
UTS125/30	125	145	16	25	5,5	600
UTS150/30	150	172	16	25	8,4	900

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses