

VICTORIA EN ISO 6134 RED

steel cord hose for saturated steam at a maximum working pressure 18 bar (261psi), used in the chemical industry, petrochemical and industrial applications in general. Not recommended for steam cleaner. The hose can be used for peaks of superheated steam at 230°C and at 18 bar. Attention: the use of superheated steam reduces the hose life. For longer life drain after use.

Hose construction

Tube: black, smooth, EPDM rubber, resistant to saturated steam.

Reinforcement: inserts of steel wire.

Cover: black, pin pricked, smooth (wrapped finish), EPDM rubber with excellent resistance to high temperatures, weathering, abrasion, and ageing.

Temperature range

-40°C to +210°C



- Flexible hose according to EN ISO 6134, for delivery of saturated steam at 210°C
- Reinforced with steel wire
- Working pressure 18bar

Number	ID mm	OD mm	WP bar	Burst pressure bar	Weight kg/m	Max lenght m
IH36801770	13	25	18	180	0,51	120
IH36801772	19	31	18	180	0,67	120
IH36801773	25	37	18	180	0,90	120
IH36801776	51	65	18	180	2,15	120

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses