




WELLFLEX® PVC XXL 343



For electrical installations, installation in switchboard plant, switch cabinets, mechanical engineering and robotics; as suction and pressure hose for gaseous and liquid media; for hydraulic and pneumatic hoses; as robust protection conduit and cable buncher

Hose construction

WELLFLEX® construction; wall thickness 1.1 mm approx.; wall: high grade soft PVC; spiral: spring steel wire firmly embedded in wall



- flexible
- gas and liquid tight
- good resistance to alkalis, acids and chemicals
- good resistance to UV and ozone
- small bending radiuses
- kink-proof
- interior protection against corrosion

Temperature range

-20 °C to +70 °C (short time +80 °C).

Number	I.D. mm	O.D. mm	connector mm	W kg	Мин R mm
343-0065-9010	65	74	74	0,74	190
343-0080-9010	80	89	89	0,96	250
343-0100-9010	100	109	109	1,19	300
343-0120-9010	120	129	129	1,42	320

Contact us:

"DAIS GLOBAL " LTD
3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
Industrial hoses
Fittings
Safety couplings
Chemical resistance table ducting hoses
Chemical resistance table hoses