

Suction and blast hose; Super-light, highly flexible + compressible 3:1

Applications: Universal suction and blast hose, especially suitable:

- for powdery solids such as dust, powder and fibres
- for gaseous media such as vapors and smoke
- for air conditioning and ventilation technique

Properties

- excellent value for money (patented process, always shipped compressed, low transport costs and risk, occupies minimal space in warehouse)
- super-light model
- highly flexible + compressible 3:1
- optimized flow properties

- good resistance to alkalis and acids
- good resistance to chemicals
- good resistance to UV and ozone
- small bending radius
- kink-proof
- gas and liquid tight
- free of phthalat
- conform to RoHS guideline
- according to the German TRBS 2153 (formerly BGR 132), the spiral can be earthed

Temperature Range

- -20 °C approx. to +70 °C approx.
- short time to +80 °C approx.

Design, material

PROTAPE® tape hose

1. spring steel wire integrated in wall
2. extruded tape
wall: high grade soft PVC
3. wall thickness 0.6 mm approx.

Delivery variants

- grey (standard)
- special colours: transparent, full coloured
- customer-specific product marking
- wall: „bioplastic“ derived from renewable raw materials

I.D. mm	O.D. mm	Rec. operating limits		Bending Radius mm	Weight kg/m	Stock Lengths m	Further Production Lengths m	Order No.
		Overpressure bar	Vacuum bar					
30	37	0,670	0,200	37	0,240	5 10	15	310-0030-0000
32	39	0,630	0,200	39	0,260	5 10	15	310-0032-0000
35	42	0,580	0,190	42	0,280	5 10	15	310-0035-0000
38	45	0,550	0,185	45	0,300	-	5 10 15	310-0038-0000
40	47	0,510	0,180	47	0,320	5 10	15	310-0040-0000
45	52	0,460	0,165	52	0,350	5 10	15	310-0045-0000
50	58	0,410	0,155	58	0,310	5 10	15	310-0050-0000
55	63	0,370	0,140	63	0,330	5 10	15	310-0055-0000
60	68	0,340	0,120	68	0,360	5 10	15	310-0060-0000
65	73	0,315	0,105	73	0,390	5 10	15	310-0065-0000
70	78	0,290	0,090	78	0,420	5 10	15	310-0070-0000
75	83	0,270	0,085	83	0,450	5 10	15	310-0075-0000
80	88	0,255	0,075	88	0,470	5 10 15	-	310-0080-0000
90	98	0,230	0,065	98	0,530	5 10	15	310-0090-0000
100	108	0,205	0,050	108	0,570	5 10 15	-	310-0100-0000
110	118	0,185	0,045	118	0,620	5 10	15	310-0110-0000
115	123	0,180	0,045	123	0,650	5 10	15	310-0115-0000
120	128	0,170	0,045	128	0,680	5 10	15	310-0120-0000
125	133	0,165	0,035	133	0,710	5 10	15	310-0125-0000
130	138	0,160	0,035	138	0,730	-	5 10 15	310-0130-0000
140	148	0,150	0,035	148	0,790	5 10	15	310-0140-0000
150	158	0,140	0,035	158	0,840	5 10	15	310-0150-0000
160	168	0,130	0,030	168	0,870	5 10	15	310-0160-0000
170	178	0,120	0,030	178	0,950	-	5 10 15	310-0170-0000
175	183	0,120	0,030	183	0,980	-	5 10 15	310-0175-0000
180	188	0,115	0,025	188	1,000	5 10	15	310-0180-0000
200	208	0,105	0,025	208	1,110	5 10	15	310-0200-0000
215	223	0,095	0,020	223	1,190	-	5 10 15	310-0215-0000
225	233	0,090	0,015	233	1,250	-	5 10 15	310-0225-0000
250	258	0,080	0,010	258	1,390	5 10	15	310-0250-0000
275	283	0,075	0,010	283	1,500	-	5 10	310-0275-0000
280	288	0,075	0,010	288	1,550	-	5 10	310-0280-0000



I.D. mm	O.D. mm	Rec. operating limits		Bending Radius mm	Weight kg/m	Stock Lengths m	Further Production Lengths m	Order No.
		Overpressure bar	Vacuum bar					
300	309	0,070	0,010	309	1,950	5 10	-	310-0300-0000
315	324	0,065	0,010	324	2,050	-	5 10	310-0315-0000
325	334	0,065	0,005	334	2,110	-	5 10	310-0325-0000
350	359	0,060	0,005	359	2,270	-	5 10	310-0350-0000
375	384	0,055	0,005	384	2,430	-	5 10	310-0375-0000
400	409	0,045	0,005	409	2,590	-	5 10	310-0400-0000
450	459	0,045	0,005	459	2,910	-	5 10	310-0450-0000
500	510	0,040	0,005	510	4,710	-	5 10	310-0500-0000

Other diameters and lengths available on request. All values indicated here are approximate figures based on a temperature of 20 °C. Data subject to change without notice. Please also refer to our Technical Appendix on www.norres.com.

Accessories

13.1.0



CLAMP 212

13.6.0




CLAMP 217

13.7.0




CLAMP 213

13.14.0



CONNECT 223

13.18.0



CONNECT 270-271

Distributed by:



Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu
 Web: <http://markuchi.eu/>

România
 Telephone/Fax : +40 21 780 45 58
 E-mail: office_ro@opwmarket.com
 Web: <http://furtunuri.eu/>

Srbija
 Telephone/Fax : 038111/2619-200
 E-mail: office_sr@opwmarket.com
 Web: <http://creva.eu/>