

MINIERA 20

Suitable for compressed air tools in factories and designed for quarries, building and mining industries. Tube resistant to traces of oil mist for medium duty.

Hose Construction

Tube: Black, oil mist resistant, smooth SBR/NBR rubber compound
 Reinforcement: Synthetic textile fabrics
 Cover: Black, abrasion, ageing and weather-resistant SBR nitrosamine free rubber compound

Temperature Range

-30 °C (-22 °F) to +80 °C (+176 °F)



- Also suitable for water and air in general service applications
- Nitrosamine free compounds
- Burst Pressure Value 3:1



Tolerances

According to RMA steel mandrel
 Refer to Technical Handbook on page TH34

Part Number	I.D. (mm)	O.D. (mm)	Working Pressure			Weight kg/m	min. Bend Radius mm	in Stock
			MPa	psi	bar			
IH36341113/40	19	30	2.0	300.0	20	0.62	190	Y
IH36341110/40	25	37	2.0	300.0	20	0.81	250	N
IH36341149/40	30	42	2.0	300.0	20	0.98	300	N
IH36341111/40	32	46	2.0	300.0	20	1.24	320	Y
IH36341121/40	38	52	2.0	300.0	20	1.43	380	Y
IH36341120/40	40	56	2.0	300.0	20	1.73	400	N
IH36341109/40	45	61	2.0	300.0	20	1.91	450	N
IH36341114/40	50	66	2.0	300.0	20	2.08	500	Y
IH36341116/40	60	76	2.0	300.0	20	2.38	600	N
IH36341117/20	75	91	2.0	300.0	20	2.89	750	N
IH36341119/20	100	118	2.0	300.0	20	4.23	1000	N

RUBBER AIR HOSE MINIERA 20 bar MADE IN ITALY



Distributed by:



Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu
 Web: http://markuchi.eu/

România
 Telephone/Fax : +40 21 780 45 58
 E-mail: office_ro@opwmarket.com
 Web: http://furtunuri.eu/

Srbija
 Telephone/Fax : 038111/2619-200
 E-mail: office_sr@opwmarket.com
 Web: http://creva.eu/