

MINIERA 40

Compressed air for mine and quarries, designed for long lasting service and maximum safety in heavy duty applications.

Hose Construction

Tube: Black, NBR rubber compound, oil resistant
 Reinforcement: One special braid of steel wire
 Cover: Black SBR/CR rubber compound, abrasion, oils, ozone and weather resistant



- Heavy duty application
- Specific for compressed air tools in mining
- Low temperature resistance
- Burst Pressure Value 4:1

Temperature Range

-40 °C (-40 °F) to +100 °C (+212 °F)

Tolerances

According to BS 5118/34310
 Refer to Technical Handbook on page TH34

Part Number	Nominal Diameter		O.D. (mm)	Working Pressure			Weight kg/m	min. Bend Radius mm	in Stock
	(mm)	(inch)		MPa	psi	bar			
IH36348001/40	13	½	23	4.0	580.0	40	0.55	150	N
IH36348002/40	19	¾	30	4.0	580.0	40	0.77	230	N
IH36348003/40	25	1	38	4.0	580.0	40	1.06	300	N
IH36348004/40	32	1 ¼	46	4.0	580.0	40	1.45	380	N
IH36348005/40	38	1 ½	52	4.0	580.0	40	1.80	455	N
IH36348000/40	51	2	66	4.0	580.0	40	2.30	600	N

RUBBER STEEL BRAIDED AIR HOSE MINIERA 40 bar MADE IN ITALY



Distributed by:



Bulgaria
 Telephone: +359 2 973 27 65
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu
 Web: http://markuchi.eu/

România
 Telephone/Fax : +40 21 780 45 58
 E-mail: office_ro@opwmarket.com
 Web: http://furtunuri.eu/

Srbija
 Telephone/Fax : 038111/2619-200
 E-mail: office_sr@opwmarket.com
 Web: http://creva.eu/