

# BIPRESS EN ISO 3821 B-R/L 20

According to EN ISO 3821

A dual line hose designed for Welding Gas equipment, cutting and allied processes.

## Hose Construction

Tube: Black, smooth SBR rubber compound, resistant to Welding Gases  
 Reinforcement: Synthetic textile yarns  
 Cover: Red and blue, ageing and abrasion-resistant, smooth SBR/EPDM rubber compound

## Temperature Range

-25 °C (-13 °F) to +80 °C (+176 °F)



- For welding in industrial and domestic application
- Colored cover following specs indication: Red for Acetylene and Blue for Oxygen
- Exceeds the standard on backfire test
- Excellent flexibility
- Burst Pressure Value 3:1

## Tolerances

According to EN ISO 3821  
 Refer to Technical Handbook on page TH34

Part Number	I.D. (mm)	O.D. (mm)	Working Pressure			Weight kg/m	min. Bend Radius mm	in Stock
			MPa	psi	bar			
IH30401107/40	6.3+6.3	13	2.0	300.0	20	0.29	–	Y
IH30401106/40	6.3+9	16	2.0	300.0	20	0.43	–	Y
IH30401108/100	8+8	15	2.0	300.0	20	0.34	–	Y
IH30401111/40	9+9	16	2.0	300.0	20	0.38	–	Y
IH30401112/100	10+10	17	2.0	300.0	20	0.46	–	N

### IMPORTANT !

Welding applications can be hazardous. Please take all the necessary safety precautions.

RUBBER HOSE – EN ISO 3821 – 2 MPa (20 bar) – I.D. MADE IN ITALY (Year with traceability code)



RUBBER HOSE – EN ISO 3821 – 2 MPa (20 bar) – I.D. MADE IN ITALY (Year with traceability code)



Distributed by:



Bulgaria  
 Telephone: +359 2 973 27 67  
 Fax: +359 2 973 26 65  
 E-mail: office@daisglobal.eu  
 Web: http://markuchi.eu/

România  
 Telephone/Fax : +40 21 780 45 58  
 E-mail: office\_ro@opwmarket.com  
 Web: http://furtunuri.eu/

Srbija  
 Telephone/Fax : 038111/2619-200  
 E-mail: office\_sr@opwmarket.com  
 Web: http://creva.eu/