

MULTIGASPRESS EN ISO 3821 NRA/L 20

According to EN ISO 3821

Suitable for all fuel gases included in the EN ISO 3821 Norm (except fluxed fuel gases) like: acetylene, LPG, MPS, natural gas, methane.

Hose Construction

Tube: Black, smooth NBR rubber compound suitable for all fuel gases included in the EN ISO 3821 Norm except fluxed fuel gases

Reinforcement: Synthetic textile yarns

Cover: Red/orange, PVC/NBR, smooth rubber compound. Resistant to ageing, weathering, pin-pricked cover to prevent blisters during use








- Pin-pricked cover
- Low permeation
- Dual colored cover following specs indication
- Flexible hose for easy handling
- Burst Pressure Value 3:1

Tolerances

According to EN ISO 3821
Refer to Technical Handbook on page TH34

Temperature Range

-25 °C (-13 °F) to +70 °C (+158 °F)

Part Number	 I.D. (mm)	 O.D. (mm)	 Working Pressure			 Weight kg/m	 min. Bend Radius mm	in Stock
			MPa	psi	bar			
IH30412960/40	6.3	13.3	2.0	300.0	20	0.17	50	N
IH30412962/40	9	16	2.0	300.0	20	0.21	70	N
IH30412964/40	12.5	22.5	2.0	300.0	20	0.41	105	N
IH30412965/40	16	25	2.0	300.0	20	0.44	150	N

RUBBER HOSE MULTIGASPRESS EN ISO 3821 - 2 MPa (20 bar) - I.D. - MADE IN ITALY - IN ITALY - Parker (the traceability code) (the traceability code)

Distributed by:



Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu
Web: http://markuchi.eu/

România
Telephone/Fax : +40 21 780 45 58
E-mail: office_ro@opwmarket.com
Web: http://furtunuri.eu/

Srbija
Telephone/Fax : 038111/2619-200
E-mail: office_sr@opwmarket.com
Web: http://creva.eu/