

CARBO G NW/L 10 – NB/R 10

According to UNI 7140

Connection of household appliances to the gas line (NW/L) or to LPG bottles (NB/R).

Hose Construction

Tube: Black, smooth NBR rubber compound, suitable for Domestic Gas
 Reinforcement: Synthetic textile yarns
 Cover: White (NW) or blue (NB), ageing-resistant, smooth (/L) or ribbed (/R) SBR/EPDM rubber compound

Temperature Range

-20 °C (-4 °F) to +90 °C (+194 °F)



- Quarterly tested by IMQ (Italian Institute of Quality Approval)
- Low permeability
- Superior tensile strength
- White smooth cover for indoor and blue ribbed cover for outdoor
- Burst Pressure Value 3:1

Tolerances

According to UNI 7140
 Refer to Technical Handbook on page TH34

Part Number	I.D. (mm)	O.D. (mm)	Working Pressure			Weight kg/m	min. Bend Radius mm	in Stock
			MPa	psi	bar			
CARBO G NB/R 10								
IH30551594/100	8	13	1.0	150.0	10	0.13	33	Y
CARBO G NW/L 10								
IH30551600/100	13	20	1.0	150.0	10	0.29	51	Y
CARBO G UNI 7140 – I.D. – IMQ – DA SOSTITUIRE ENTRO IL ... - MADE IN ITALY							Parker	
CARBO G UNI 7140 – I.D. – IMQ – DA SOSTITUIRE ENTRO IL ... - MADE IN ITALY							Parker	

Distributed by:



Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu
 Web: http://markuchi.eu/

România
 Telephone/Fax : +40 21 780 45 58
 E-mail: office_ro@opwmarket.com
 Web: http://furtunuri.eu/

Srbija
 Telephone/Fax : 038111/2619-200
 E-mail: office_sr@opwmarket.com
 Web: http://creva.eu/