

IR IRRIGATION PU HOSE

A standard duty irrigation hose for water discharge and transfer in agricultural applications.

Hose Construction

Polyurethane extruded through one woven polyester ply of reinforcement

Temperature Range

-40 °C (-40 °F) to +80 °C (+176 °F)



- Much easier to couple, install and remove than polyethylene pipe
- High performing polymer preserve from fluid contamination
- Excellent resistance to abrasion
- Burst Pressure Value 2:1

| Part Number | Nominal Diameter | | Wall (mm) | Working Pressure | | | Weight kg/m | min. Bend Radius mm | in Stock |
|-------------|------------------|--------|-----------|------------------|-------|-----|----------------|------------------------|----------|
| | (mm) | (inch) | | MPa | psi | bar | | | |
| IR20X200MB | 51 | 2 | 2.30 | 3.1 | 450.0 | 31 | 0.41 | - | N |
| IR25X200MB | 63.5 | 2 ½ | 2.30 | 3.1 | 450.0 | 31 | 0.58 | - | N |
| IR30X200MB | 76 | 3 | 3.30 | 2.4 | 350.0 | 24 | 0.75 | - | Y |
| IR35X200MB | 90 | 3 ½ | 3.30 | 1.7 | 250.0 | 17 | 0.97 | - | Y |
| IR40X200MB | 102 | 4 | 3.30 | 1.7 | 250.0 | 17 | 1.14 | - | Y |
| IR45X200MB | 114 | 4 ½ | 3.30 | 1.7 | 250.0 | 17 | 1.25 | - | Y |
| IR50X200MB | 127 | 5 | 3.30 | 1.7 | 250.0 | 17 | 1.42 | - | Y |
| IR60X200MB | 152 | 6 | 3.05 | 2.0 | 300.0 | 20 | 1.72 | - | Y |



Parker - SNAP-TITE (PART NUMBER) (DATE CODE) MADE IN IRELAND MAXIMUM WORKING PRESSURE (XXX) PSI

Distributed by:



Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu
Web: http://markuchi.eu/

România
Telephone/Fax : +40 21 780 45 58
E-mail: office_ro@opwmarket.com
Web: http://furtunuri.eu/

Srbija
Telephone/Fax : 038111/2619-200
E-mail: office_sr@opwmarket.com
Web: http://creva.eu/