

# THERMOPRESS 10

Suitable for delivery of hot water, non-aggressive hot liquids and steam to a maximum temperature of +120 °C (+248 °F). To connect boilers to air conditioning units and for hot water cleaning systems.

## Hose Construction

Tube: Black, smooth, heat resistant, EPDM nitrosamine free rubber compound  
 Reinforcement: Synthetic textile fabrics or yarns  
 Cover: Black, smooth, heat, ageing and weather-resistant EPDM nitrosamine free rubber compound

## Temperature Range

-40 °C (-40 °F) to +100 °C (+212 °F),  
 with peaks +120 °C (+248 °F)



- Robust structure
- Wide temperature range
- Nitrosamine free
- Burst Pressure Value 4:1



## Tolerances

I.D. ≤ 22 mm according to UNI EN ISO 1307  
 I.D. > 22 mm according to RMA steel mandrel  
 Refer to Technical Handbook on page TH34

Part Number	I.D. (mm)	O.D. (mm)	Working Pressure			Weight kg/m	min. Bend Radius mm	in Stock
			MPa	psi	bar			
IH36800002/100	12	22.5	1.0	150.0	10	0.38	120	Y
IH36800003/80	15	25.5	1.0	150.0	10	0.44	150	Y
IH36800004/80	18	28.5	1.0	150.0	10	0.51	180	Y
IH36800005/80	20	30.5	1.0	150.0	10	0.56	200	Y
IH36800006/40	25	35	1.0	150.0	10	0.61	250	Y
IH36800007/40	30	41	1.0	150.0	10	0.79	300	Y
IH36800009/40	40	54	1.0	150.0	10	1.34	400	Y
IH36800011/40	50	68	1.0	150.0	10	2.12	500	Y
IH36800012/40	60	82	1.0	150.0	10	3.10	600	N

RUBBER HOSE THERMOPRESS 10 bar MADE IN ITALY



Distributed by:



Bulgaria  
 Telephone: +359 2 973 27 67  
 Fax: +359 2 973 26 65  
 E-mail: office@daisglobal.eu  
 Web: http://markuchi.eu/

România  
 Telephone/Fax : +40 21 780 45 58  
 E-mail: office\_ro@opwmarket.com  
 Web: http://furtunuri.eu/

Srbija  
 Telephone/Fax : 038111/2619-200  
 E-mail: office\_sr@opwmarket.com  
 Web: http://creva.eu/