

DRINKPRESS 164

Recommended for delivery of all foodstuffs containing animal or vegetable fats and oils as well as beverages and liqueurs. Ideal for cleaning dairies, slaughter houses, food processing plants with hot water and steam.

Hose Construction

Tube: White, smooth NBR rubber compound, non-toxic, odorless and taste-free.
Resistant to steam and hot water

Reinforcement: Synthetic textile yarns

Cover: Blue, smooth NBR/PVC rubber compound. Oils, grease, abrasion and weather-resistant. Pin-pricked cover to prevent blisters during use.



- According to FDA, DM 21/03/73
- Versatility of use for a logistic benefit
- Burst Pressure Value 3:1 for water
- Burst Pressure Value 10:1 for steam

Tolerances

According to UNI EN ISO 1307
Refer to Technical Handbook on page TH34

Temperature Range

-20 °C (+4 °F) to +95 °C (+203 °C) for foodstuffs
up to +164 °C (+327 °F) for hot water & steam only

For foodstuffs

Part Number	I.D. (mm)	O.D. (mm)	Working Pressure			Weight kg/m	min. Bend Radius mm	in Stock
			MPa	psi	bar			
IH30240051/40	10	19	2.0	300.0	20	0.31	80	N
IH30240052/40	13	23	2.0	300.0	20	0.42	105	Y
IH30240053/40	16	26	2.0	300.0	20	0.49	130	N
IH30240054/40	19	31	2.0	300.0	20	0.71	150	Y
IH30240055/40	25	39	1.0	150.0	10	1.05	200	N

For hot water & steam

Part Number	I.D. (mm)	O.D. (mm)	Working Pressure			Weight kg/m	min. Bend Radius mm	in Stock
			MPa	psi	bar			
IH30240051/40	10	19	0.6	87.0	6	0.31	80	N
IH30240052/40	13	23	0.6	87.0	6	0.42	105	Y
IH30240053/40	16	26	0.6	87.0	6	0.49	130	N
IH30240054/40	19	31	0.6	87.0	6	0.71	150	Y
IH30240055/40	25	39	0.3	44.0	3	1.05	200	N

RUBBER HOSE DRINKPRESS 164

50A - D.M. 21/03/73

Parker IN ITALY

Distributed by:



Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu
Web: http://markuchi.eu/

România
Telephone/Fax: +40 21 780 45 58
E-mail: office_ro@opwmarket.com
Web: http://furtunuri.eu/

Srbija
Telephone/Fax: 038111/2619-200
E-mail: office_sr@opwmarket.com
Web: http://creva.eu/