

ASPIREX

Suitable for suction of air, dust, fumes, saw-dust and wood-shavings. Also suitable for centralized suction equipment in wood, textile, china and welding equipment. It is also suitable for use on agricultural machinery.

Hose Construction

Flexible hose having a grey, rigid PVC spiral embedded in a metalized grey, flexible PVC wall. Externally corrugated, smooth inner surface. Self-extinguishing according to UL 94 Class V2.

Temperature Range






-15 °C (+5 °F) to +60 °C (+140 °F)



- Self-extinguishing hose
- General purpose hose
- Not to be used under pressure
- Vacuum 0.75 bar for ID up to 50 mm then 0.40 bar

Tolerances

Refer to Technical Handbook on page TH34

Part Number	 I.D. (mm)	 Wall (mm)	 Working Pressure			 Weight kg/m	 min. Bend Radius mm	in Stock
			MPa	psi	bar			
IH35560020/50	20	2.6	-	-	-	0.14	20	Y
IH35560025/50	25	2.9	-	-	-	0.18	25	Y
IH35562032/50	32	3.3	-	-	-	0.27	32	Y
IH35560040/50	40	3.9	-	-	-	0.36	40	Y
IH35560050/50	50	4.2	-	-	-	0.52	50	Y
IH35560060/50	60	4.4	-	-	-	0.64	60	Y
IH35560070/50	70	4.8	-	-	-	0.76	70	Y
IH35560080/50	80	5.0	-	-	-	0.97	80	Y
IH35560100/30	100	5.3	-	-	-	1.27	100	Y
IH35560120/30	120	5.6	-	-	-	1.58	120	Y
IH35560150/30	150	5.9	-	-	-	2.15	150	Y
IH35562160/30	160	6.1	-	-	-	2.28	160	N
IH35560200/15	200	7.0	-	-	-	2.95	200	Y
IH35560250/15	250	8.0	-	-	-	4.00	250	N

ASPIREX I.D. mm - SELF-EXTINGUISHING UL 94 V2 PARKER

Distributed by:



Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu
Web: http://markuchi.eu/

România
Telephone/Fax : +40 21 780 45 58
E-mail: office_ro@opwmarket.com
Web: http://furtunuri.eu/

Srbija
Telephone/Fax : 038111/2619-200
E-mail: office_sr@opwmarket.com
Web: http://creva.eu/