

OILPRESS N/L 20 - 30

Suitable for multi-purpose applications requiring transfer of many types of fluids and for petroleum products with aromatic content not exceeding 50 %.

Hose Construction

Tube: Smooth, black, oil and fuel resistant NBR rubber compound, suitable for petroleum products with aromatic content not exceeding 50 %

Reinforcement: Synthetic textile yarns

Cover: Smooth, black, self-extinguishing, antistatic ($R < 1 \text{ M}\Omega/\text{m}$) heat, oil, abrasion and weather resistant CR rubber compound



- Agriculture, construction and general industrial
- Suitable for many different fuels included Biodiesel B100
- Two different Working Pressure lines
- Wide range temperature
- Burst Pressure Value 3:1

Tolerances

According to UNI EN ISO 1307
Refer to Technical Handbook on page TH34

Temperature Range

-30 °C (-22 °F) to +100 °C (+212 °F),
with peaks up to +120 °C (+248 °F) for oil

| Part Number | I.D. (mm) | O.D. (mm) | Working Pressure | | | Weight kg/m | min. Bend Radius mm | in Stock |
|-----------------|-----------|-----------|------------------|-------|-----|----------------|------------------------|----------|
| | | | MPa | psi | bar | | | |
| OILPRESS N/L 20 | | | | | | | | |
| IH30832000/40 | 6 | 12 | 2.0 | 300.0 | 20 | 0.12 | 25 | Y |
| IH30832001/40 | 8 | 14 | 2.0 | 300.0 | 20 | 0.15 | 35 | Y |
| IH30832002/40 | 10 | 17 | 2.0 | 300.0 | 20 | 0.21 | 40 | Y |
| IH30832003/40 | 13 | 20 | 2.0 | 300.0 | 20 | 0.26 | 55 | Y |
| IH30832004/40 | 16 | 23 | 2.0 | 300.0 | 20 | 0.31 | 65 | Y |
| IH30832005/40 | 19 | 28 | 2.0 | 300.0 | 20 | 0.47 | 80 | Y |
| IH30832006/40 | 25 | 36 | 2.0 | 300.0 | 20 | 0.74 | 100 | Y |
| OILPRESS N/L 30 | | | | | | | | |
| IH30832031/40 | 6 | 14 | 3.0 | 450.0 | 30 | 0.18 | 25 | N |
| IH30832032/40 | 8 | 16 | 3.0 | 450.0 | 30 | 0.21 | 30 | Y |
| IH30832038/40 | 9 | 17 | 3.0 | 450.0 | 30 | 0.24 | 35 | N |
| IH30832033/40 | 10 | 18 | 3.0 | 450.0 | 30 | 0.25 | 40 | Y |
| IH30832034/40 | 13 | 23 | 3.0 | 450.0 | 30 | 0.40 | 55 | Y |
| IH30832035/40 | 16 | 27 | 3.0 | 450.0 | 30 | 0.47 | 65 | N |
| IH30832036/40 | 19 | 30 | 3.0 | 450.0 | 30 | 0.60 | 80 | N |
| IH30832037/40 | 25 | 37 | 3.0 | 450.0 | 30 | 0.83 | 100 | N |

RUBBER HOSE OILPRESS W.P. bar R<1M Ω MADE IN ITALY

Distributed by:



Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu
Web: http://markuchi.eu/

România
Telephone/Fax : +40 21 780 45 58
E-mail: office_ro@opwmarket.com
Web: http://furtunuri.eu/

Srbija
Telephone/Fax : 038111/2619-200
E-mail: office_sr@opwmarket.com
Web: http://creva.eu/