

ARCTIC-EDGE

Parker Global Product

Recommended suitable for air, mild chemicals, water, oil, biodiesel, diesel, ethanol and gasoline to be used in refrigerated applications and cold weather conditions. For agriculture, construction and general industrial. Do not use for fuel dispensing.

Hose Construction

Tube: Black NBR rubber compound.
 Reinforcement: Multiple textile plies with static wire
 Cover: Black, smooth CR rubber compound resistant to oil and weathering

Temperature Range

-57 °C (-70 °F) to +100 °C (+212 °F)



- High flexibility and kink resistance at extreme low temperatures
- Conductive hose with copper wire
- Cover incorporates a longitudinal blue stripe for easy identification
- Burst Pressure Value 4:1

Tolerances

According to UNI EN ISO 1307
 Refer to Technical Handbook on page TH34

Part Number	I.D. (mm)	O.D. (mm)	Working Pressure			Weight kg/m	min. Bend Radius mm	in Stock
			MPa	psi	bar			
IH710238304/40	9.5	19	2.0	300.0	20	0.10	96	N
IH710250304/40	13	23	2.0	300.0	20	0.13	127	N
IH710275304/40	19	29.5	2.0	300.0	20	0.17	152	Y
IH7102100304/40	25	37	2.0	300.0	20	0.24	203	Y
IH7102125304/40	32	46	2.0	300.0	20	0.38	228	Y
IH7102138304/40	35	49	2.0	300.0	20	0.40	241	N
IH7102150304/40	38	51.5	2.0	300.0	20	0.42	254	Y

SERIES 7102**ARTIC -EDGE** -70°F (-57°C) LOW-TEMP ...ID (... mm) 300 PSI (20 bar) MAX WP

Distributed by:



Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu
 Web: http://markuchi.eu/

România
 Telephone/Fax : +40 21 780 45 58
 E-mail: office_ro@opwmarket.com
 Web: http://furtunuri.eu/

Srbija
 Telephone/Fax : 038111/2619-200
 E-mail: office_sr@opwmarket.com
 Web: http://creva.eu/