

CARBOPRESS D EN 1360/1

According to EN 1360 type 1

Designed for dispensing metered quantities of automotive fuels from dispensing equipment (petrol pumps). Resistant to leaded and unleaded petrol (gasoline) with an aromatic content not exceeding 50 %.

Hose Construction

Tube:	Black, smooth, NBR rubber compound, antistatic ($R < 1 \text{ M}\Omega/\text{m}$)
Reinforcement:	Synthetic textile yarns providing low dilation. Built-in copper wires to allow electrical continuity between fittings
Cover:	Black, smooth, non-staining and antistatic ($R < 1 \text{ M}\Omega/\text{m}$) CR rubber compound resistant to abrasion, oil, fuel and weathering

Temperature Range

-25 °C (-13 °F) to +55 °C (+131 °F)



- Electrical continuity guaranteed by copper wires if correctly assembled
- Designed for petrol pumps
- Suitable for diesel and gasoline
- Burst Pressure Value 4:1

Tolerances

On inside diameter	
≤ I.D. 19 mm	± 0.80 mm
> I.D. 19 mm	± 1.25 mm
On outside diameter	
≤ O.D. 31 mm	± 0.80 mm
> O.D. 31 mm	± 1.25 mm
Length tolerance	± 1 %

Part Number	Dimensions		Working Pressure			Weight kg/m	min. Bend Radius mm	in Stock
	I.D. (mm)	O.D. (mm)	MPa	psi	bar			
IH30502420/90	16	26	1.6	232.0	16	0.47	80	Y
IH30502421/80	18	30	1.6	232.0	16	0.64	90	Y
IH30502407/50	19	31	1.6	232.0	16	0.63	95	Y
IH36521140/40*	25	37	1.6	232.0	16	0.74	150	Y

* CARBOCORD D EN1360/1 Mandrel Made Production

CARBOPRESS D EN 1360:2005 Type 1 - I.D.mm - 16 bar - M - MADE IN ITALY
Quarter/Year with traceability code



CARBOPRESS D EN 1360:2005 Type 1 M - I.D. mm - 16 bar - Quarter/Year - MADE IN ITALY



Distributed by:



Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu
Web: http://markuchi.eu/

România
Telephone/Fax : +40 21 780 45 58
E-mail: office_ro@opwmarket.com
Web: http://furtunuri.eu/

Srbija
Telephone/Fax : 038111/2619-200
E-mail: office_sr@opwmarket.com
Web: http://creva.eu/