

PERFORMER GL AD10P



CONSTRUCTION & ENVIRONMENT

Abrasive materials hydraulic and pneumatic handling

Applications

Pneumatic suction or discharge of abrasive materials.

Advantages

- Excellent resistance to abrasion.
- Hose can be supplied cut to length for on-site coupling.
- Quick and easy hose installation.
- Light weight and low bending radius.
- Low installation cost.
- Electrical continuity (mandatory for pneumatic handling) is ensured by braid and the helix.
- Suppression of pressure surges.
- Reduction in pressure head loss.
- Damping of vibrations and noise.
- Excellent weather resistance.

Technical description

Inner tube: wear resistant NR, tan, smooth.

Reinforcement: synthetic textile with embedded steel helix.

Cover: weather resistant EPDM, black, corrugated, fabric impression.

Temperature range: - 30 °C to + 70 °C.

Electrical properties: built-in conductive wire (helix must be connected with couplings).

Couplings/Fittings

Hoses are fitted with BLOC-END® and must be used to the following maximum working pressure:

ID ≤ 150 mm: WP = 10 bar,

ID > 150 mm: WP = 5 bar.

Complementary information

Low stretch under 10 bar working pressure.

Lengths are stocked in 20 or 12 m, ask us for longer lengths.

PERFORMER GL AD10P

11/06/2013

ID mm	OD mm	Working pressure bar	Bursting pressure bar	Max. vacuum bar	Bending radius mm	Weight kg/m	Max. length m	Article number	Stock (■) or min. order m
25	-0/+1 53 ±2	10	30	0.9	125	1.9	20	0128521	20
32	-0/+1 60 ±2	10	30	0.9	160	2.2	20	0128531	20
40	-0/+1 73 ±2	10	30	0.9	200	3.2	20	0128532	20
50	-0/+1 83 ±2	10	30	0.9	250	3.6	20	0061629	■
65	-0/+1 98 ±2	10	30	0.9	325	4.4	20	0061630	■
80	-0/+1 113 ±2	10	30	0.9	400	5.2	20	0061631	■
100	-0/+1 133 ±2	10	30	0.9	500	6.3	20	0061632	■
125	-0/+1 158 ±2	10	30	0.9	750	7.7	20	0061633	■
150	-0/+1 183 ±2	10	30	0.9	1050	9	20	0061634	80
200	-0/+2 234.5 ±2	10	30	0.9	1600	14.5	12	0122700	36
250	-0/+2 285.5 ±2	10	30	0.9	2000	16.8	12	0122746	36
300	-0/+2 340.5 ±2	10	30	0.9	2500	23.5	12	0122757	12
350	-0/+2 391 ±3	10	30	0.9	3100	30.2	12	5513022	12

Branding



and embossed: week/year - CONDUCTEUR

Distributed by:



Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu
Web: http://markuchi.eu/

România
Telephone/Fax : +40 21 780 45 58
E-mail: office_ro@opwmarket.com
Web: http://furtunuri.eu/

Srbija
Telephone/Fax : 038111/2619-200
E-mail: office_sr@opwmarket.com
Web: http://creva.eu/