

PULSOR 125

CONSTRUCTION & ENVIRONMENT

Concrete pump and placement



Applications

Concrete pump hose for boom transfer, placement.
Also for mortar, grout, slurry, and pneumatic discharge of cement and minerals.

Advantages

- Highly abrasion resistant hose to give extended service life.
- Flexible and easy to handle.
- Robust construction to withstand heavy compressive loads to guarantee maximum safety.
- Construction eliminates kinking and allows easy cleaning by reverse pumping.

Technical description

Inner tube: wear resistant NR, black, smooth.
Reinforcement: two steel cords plies for ID \leq 65 mm and four steel cords plies for ID \geq 76.2 mm.
Cover: wear and weather resistant NR, black, fabric impression.
Temperature range: - 30 °C to + 80 °C.

Couplings/Fittings

Swaged couplings with dimensions according to VICTAULIC or concrete pump manufacturers (PUTZMEISTER, SCHWING ...).

PULSOR 125

26/02/2008

ID	Wall thickness		OD		Working pressure	Bursting pressure	Max. vacuum	Bending radius	Weight	Length	Article number	Stock (■) or min. order
mm	mm	mm	mm	mm	bar	bar	bar	mm	kg/m	m		m
50.0	9.0	± 0.75	68.0	± 1.50	70	125	0.8	200	2.24	20	0060005	■
65.0	10.0	± 0.75	85.0	± 1.50	70	125	0.8	250	3.88	20	0060007	■
76.2	12.4	± 0.75	101.0	± 1.50	70	125	0.8	270	4.96	20	0060418	■
101.6	13.7	± 0.75	129.0	± 1.75	70	125	0.8	300	7.08	20	0060420	■
125.0	15.5	± 0.75	156.0	± 2.00	70	125	0.8	360	9.83	20	0060422	■
150.0	17.5	± 0.75	185.0	± 2.00	70	125	0.8	570	13.34	20	0060423	■

Branding



and embossed for ID from 25 to 65 mm: TRELLEBORG - PULSOR 125 - Made in France - month/year
and embossed for ID from 76.2 to 150 mm: TRELLEBORG - PULSOR 125 - ND mm /" - WP 42 bar/600 PSI - Lbs/Ft - FWC - week/year

Distributed by:



Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu
Web: http://markuchi.eu/

România
Telephone/Fax : +40 21 780 45 58
E-mail: office_ro@opwmarket.com
Web: http://furtunuri.eu/

Srbija
Telephone/Fax : 038111/2619-200
E-mail: office_sr@opwmarket.com
Web: http://creva.eu/