

TRELLSLUMP



CONSTRUCTION & ENVIRONMENT

Concrete pump and placement

Applications

Lay flat hose for concrete skip.
For discharge to concrete form.

Advantages

- Coil flat for easy storage and handling.
- Flexible, lightweight hose.
- Excellent resistance to wear, abrasion and weather.

Technical description

Inner tube: SBR, black, smooth.

Reinforcement: synthetic textile.

Cover: SBR, black, fabric impression.

Temperature range: -30 °C to +90 °C.

TRELLSLUMP

28/02/2014

ID mm	Wall thickness mm	OD mm	Working pressure bar	Bursting pressure bar	Weight kg/m	Length m	Article number	Stock (■) or min. order m
152	2.7	157.4	3	10	1.6	40	5501039	40
204	4.5	213	3	10	3.8	40	5501040	■
254	4.5	263	3	10	4.7	40	5501041	■

Branding

No branding

Distributed by:



Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu
Web: http://markuchi.eu/

România
Telephone/Fax : +40 21 780 45 58
E-mail: office_ro@opwmarket.com
Web: http://furtunuri.eu/

Srbija
Telephone/Fax : 038111/2619-200
E-mail: office_sr@opwmarket.com
Web: http://creva.eu/