

GASSOFLEX SSE



Aplicaciones

Gassoflex SSE es recomendada para la impulsión y/o aspiración de una gran variedad de productos químicos compatibles con el polipropileno y el inoxidable y que tengan contacto con la manguera tanto interior como exteriormente, en camiones cisternas, vagones o en planta.

SSE

Serie Standard: 10100

Serie Pesada: 14100

Construcción

- Espiral Interior: Acero inoxidable 316 (S)
- Espiral Exterior: Acero inoxidable 316 (S)
- Forro Interior: Polipropileno (E)
- Cubierta: Polipropileno

Gama de Temperatura 20°C a +100°C

Factor de Seguridad

La presión de trabajo está basada en un factor de seguridad 5:1

Applications

Gassoflex SSE is recommended for the delivery and/or suction of a wide range of chemical products compatible with any polypropylene and stainless steel which may come in contact with the hose both internally or externally in tank trucks, railcars or fixed deposits.

SSE

Standard Series: 10100

Heavy Series: 14100

Construction

- Inner Wire spiral: Stainless Steel 316 (S)
- Outer Wire spiral: Stainless Steel 316 (S)
- Inner Lining: Polypropylene (E)
- Cover: Polypropylene

Temperature range 20°C a +100°C

Work Safety factor

The working pressure is based on a safety factor of 5:1

| Código Gassó Gassó code | Presión trabajo Working press. | | Diámetro Diameter | Radio curvatura Curve radius | Peso Weight | Longitud máx. rollos Max. coil lengths |
|----------------------------|-----------------------------------|-------|----------------------|---------------------------------|----------------|---|
| | (bar) | (PSI) | | | | |

GASSOFLEX 10100 SSE

| | | | | | | |
|--------|----|-----|-------|-----|------|----|
| AIA325 | 10 | 150 | 1 | 68 | 0,85 | 35 |
| AIA332 | 10 | 150 | 1 1/4 | 74 | 1,07 | 35 |
| AIA340 | 10 | 150 | 1 1/2 | 105 | 1,50 | 35 |
| AIA350 | 10 | 150 | 2 | 190 | 2,00 | 35 |
| AIA351 | 10 | 150 | 2 1/2 | 225 | 3,05 | 35 |
| AIA375 | 10 | 150 | 3 | 290 | 3,55 | 35 |
| AIA400 | 10 | 150 | 4 | 320 | 6,40 | 35 |

GASSOFLEX 14100 SSE

| | | | | | | |
|---------|----|-----|-------|-----|------|----|
| — | 14 | 210 | 1 | 68 | 0,85 | 35 |
| — | 14 | 210 | 1 1/4 | 74 | 1,07 | 35 |
| — | 14 | 210 | 1 1/2 | 105 | 1,50 | 35 |
| — | 14 | 210 | 2 | 190 | 2,00 | 35 |
| — | 14 | 210 | 2 1/2 | 225 | 3,05 | 35 |
| — | 14 | 210 | 3 | 290 | 3,55 | 35 |
| AIA4000 | 14 | 210 | 4 | 320 | 6,40 | 35 |

Distributed by:



Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu
Web: http://markuchi.eu/

România
Telephone/Fax : +40 21 780 45 58
E-mail: office_ro@opwmarket.com
Web: http://furtunuri.eu/

Srbija
Telephone/Fax : 038111/2619-200
E-mail: office_sr@opwmarket.com
Web: http://creva.eu/