



**AIRDUC® PUR 355 CSH
REINFORCED**




Abrasion-proof suction and transport hose, especially suitable:
 • for public utility street cleaning vehicles

Hose construction

Wall 1.5 – 1.8 mm.

Temperature range

-40 °C ÷ +90°C; with peaks up to +125 °C



- heavy model
- highly flexible + compressible
- extremely abrasion-proof with reinforcement underneath wire and narrow hose pitch

No	I.D. mm	O.D. mm	Pressure bar	Vacuum bar	Bend radius mm	Weight kg/m	Max length m
355-0200-5015	200	212	0,374	0,120	275	2,630	5 1 0
355-0208-5015	208	220	0,360	0,120	286	2,740	5 10
355-0255-5016	255	267	0,295	0,075	347	3,580	5 1 0
355-0350-5015	350	365	0,220	0,050	475	6,400	5 10
355-0352-5013	352	367	0,215	0,050	477	6,440	5 1 0

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5
 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

- Ducting hoses
- Industrial hoses
- Fittings
- Safety couplings
- Chemical resistance table ducting hoses
- Chemical resistance table hoses