



AIRDUC® PUR 355 CSH




Abrasion-proof suction and transport hose, especially suitable:

- for public utility street cleaning vehicles

Hose construction

Wall 1.5mm.



Temperature range

-40 °C ÷ +90°C; with peaks up to +125 °C



- heavy model
- highly flexible + compressible
- extremely abrasion-proof with reinforcement underneath wire and narrow hose pitch

No	I.D. mm	O.D. mm	Pressure bar	Vacuum bar	Bend radius mm	Weight kg/m	Max length m
355-0200-5200	200	213	0,375	0,120	416	3,120	5 10
355-0206-5200	206	219	0,365	0,120	438	3,210	5 10
355-0225-5200	225	238	0,335	0,100	476	3,500	5 10
355-0257-5200	257	270	0,290	0,075	540	3,980	5 10
355-0280-5200	280	293	0,265	0,070	586	4,330	5 10
355-0400-5200	400	413	0,180	0,040	816	6,850	5 10

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5
 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses