



ARCTIC EDGE

Recommended suitable for air, mild chemicals, water, oil, biodiesel, diesel, ethanol and gasoline to be used in refrigerated applications and cold weather conditions. For agriculture, construction and general industrial. Do not use for fuel dispensing.

Hose construction

Tube: Black NBR rubber compound.

Reinforcement: Multiple textile plies with static wire

Cover: Black, smooth CR rubber compound resistant to oil and weathering



- High exibility and kink resistance at extreme low temperatures
- Conductive hose with copper wire
- Cover incorporates a longitudinal blue stripe for easy identi-cation
- Burst Pressure Value 4:1

Temperature range

-57°C to +100°C

According to

UNI EN ISO 1307

Number	I.D.	O.D.	WP	BP	Weight	R min
	mm	mm	bar	bar	kg	mm
IH710238304/40	9.5	19	20	60	0.10	96
IH710250304/40	13	23	20	60	0.13	127
IH710275304/40	19	29.5	20	60	0.17	152
IH7102100304/40	25	37	20	60	0.24	203
IH7102125304/40	32	46	20	60	0.38	228
IH7102138304/40	35	49	20	60	0.40	241
IH7102150304/40	38	51.5	20	60	0.42	254

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses