



ASPIREX 140°

Suction hose for: air, smoke, vapours, exhaust gas, dust, chips, grains, pellets.

Good resistance to acids and lyes, resistant also to polychloroprene (CR), against hydrocarbons, oils. Very good resistance also to abrasion, atmospheric and ageing conditions. Oil resistant as per ASTM D 2000.

Recommendation: the hose has to be used in static conditions and not in dynamic conditions.

Hose construction

Black hose in Santoprene with an integrated steel spiral.



- Multiple media suction hose
- Oil resistant - ASTM D 2000
- Designed for high temperature application
- Not to be used under pressure
- Vacuum 0.3 bar for ID up to 50 mm

Temperature range

-40°C ÷ +140°C with peaks up to 150°C

No	ID mm	Wall mm	WP bar	Vacuum bar	Weight kg	R min mm
IH35579040/30	40	3	-	0,3	0,20	46
IH35579050/30	50	3	-	0,3	0,28	56
IH35579063/30	63	3	-	0,25	0,34	69
IH35579080/30	80	3,5	-	0,25	0,48	87
IH35579090/30	90	3,5	-	0,25	0,52	97
IH35579100/30	100	3,5	-	0,25	0,66	107
IH35579110/30	110	3,5	-	0,25	0,72	117
IH35579125/30	125	3,5	-	0,25	0,80	132
IH35579150/30	150	3,5	-	0,25	1,10	157

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5
 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses