



ASPIREX PU/ANC

Suitable for suction of warm air, abrasion dust, warm fumes, saw-dust, wood-shavings, cement, cereal grains, sugar, and other granules.

Hose construction

PU transparent and antistatic hose having a grey, rigid PVC spiral, resistant to crush, abrasion and ozone, with antistatic 9 wires copper cord.

Food and beverage – The polyurethane used is in conformity to:

– F.D.A. – CFR 21parts 175, 105, 177, 1680, 177, 2600;

– CEE82/711, 85/572, 89/109, 90/128, 92/30, 93/8, 95/3, 98/11

Temperature range

-25 °C ÷ +85 °C



- In conformity with FDA title 21 and multiple EC specs
- Strong triene resistance
- Not to be used under pressure
- Vacuum 0.5 bar for ID up to 32 mm then 0.40 bar

No	ID mm	Wall mm	WP bar	Vacuum bar	Weight kg	Bend radius mm
IH35576038/20	40	3	-	0,3	0,20	46
IH35576050/20	50	3	-	0,3	0,28	56
IH35576060/20	63	3	-	0,25	0,34	69
IH35576080/20	80	3,5	-	0,25	0,48	87
IH35576102/20	90	3,5	-	0,25	0,52	97

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5
 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses