



AUTOGAS ECE 67/110 CLASS 2

Low pressure hoses, designed according to regulation ECE 67, 01, Annex 8, Class 2 and ECE 110, 02, Annex 4b, Class 2.

Suitable for low pressure delivery of LPG and methane CNG alternative fuel kits.

Hose construction

Tube: Black, smooth, insulating (R > 1 M/m), LPG and methane permeation resistant NBR rubber compound

Reinforcement: Synthetic textile yarns

Cover: Black, smooth, insulating (R > 1 M/m), CSM rubber compound resistant to ageing, heat, abrasion, ozone and weathering.

Temperature Range

-30°C ÷ +125°C

Tolerances no

UNI EN ISO 1307/97



- Insulating cover and tube compounds
- Exceeds DIN 4815 Teil 4
- Available pre-formed on request
- Very low permeation values closed to zero
- Burst Pressure Value 4:1

According to

ECE 67 and ECE 110 Class 2

Number	ID mm	OD mm	WP bar	BP bar	Weight kg	R min mm
IH30510060/50	4	10	4.5	13.5	0.09	35
IH30510027/50	5	10.5	4.5	13.5	0.09	40
IH30510062/50	6	13	4.5	13.5	0.14	50
IH30510064/50	10	17	4.5	13.5	0.20	80
IH30510065/50	12	19	4.5	13.5	0.23	100
IH30510066/50	14	22	4.5	13.5	0.30	115
IH30510067/50	16.5	24.5	4.5	13.5	0.34	135
IH30510069/50	19	27	4.5	13.5	0.39	150

Contact us:

"DAIS GLOBAL " LTD

3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria

Telephone: +359 2 973 27 67

Fax: +359 2 973 26 65

E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses

Industrial hoses

Fittings

Safety couplings

Chemical resistance table ducting hoses

Chemical resistance table hoses