

AVIO GLOBAL C

Flexible hose for the ground fuelling of aircrafts, type C, suitable to be rolled up onto reels and abrasion resistant. Softwall hose designed for the ground fuelling of aircrafts. The hose can be rolled up onto reels and is suitable to convey petroleum products and jet A1 fuel with aromatic content up to 50%.

Hose construction

Tube: extruded, black, smooth, NBR rubber.

Reinforcement: high strength synthetic cord.

Cover: black, smooth (wrapped finish), antistatic synthetic rubber, resistant to weathering, abrasion and traces of oil.

Temperature range

-25°C to +70°C



- Ground fuelling of aircrafts
- Electrically conductive
- Working pressure 20 bar

Number	ID mm	OD Mm	WP bar	Burst pressure bar	Weigh t Kg/m	Min. reel size mm	Max lenght m
HB50	19	32	20	80	0,59	225	60
HD025C	25	38	20	80	0,73	300	60
HD032C	32	45	20	80	0,89	375	60
HD038C	38	52	20	80	1,07	450	60
HD050C	50	67	20	80	1,70	550	60
HD063C	63,5	80	20	80	2,06	600	60
HD075C	75	91	20	80	2,32	600	60
HD100C	100	118	20	80	3,37	900	60

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses