



BIPRESS EN ISO 3821 B-R/L 20

A dual line hose designed for Welding Gas equipment, cutting and allied processes.

Hose constructon

Tube: Black, smooth SBR rubber compound, resistant to Welding Gases

Reinforcement: Synthetic textile yarns

Cover: Red and blue, ageing and abrasionresistant, smooth SBR/EPDM rubber compound

Temperature range

-25 °C ÷ +80 °C



- For welding in industrial and domestic application
- Colored cover following specs indication: Red for Acetylene and Blue for Oxygen
- Exceeds the standard on backre test
- Excellent -exibility
- Burst Pressure Value 3:1

According to
EN ISO 3821

Number	I.D. mm	O.D. mm	WP bar	BP bar	Weight kg	Min R mm
IH30401107/40	6.3+6.3	13	20	60	0.29	-
IH30401106/40	6.3+9	16	20	60	0.43	-
IH30401108/100	8+8	15	20	60	0.34	-
IH30401111/40	9+9	16	20	60	0.38	-
IH30401112/100	10+10	17	20	60	0.46	-

Contact us:

"DAIS GLOBAL " LTD
3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
Industrial hoses
Fittings
Safety couplings
Chemical resistance table ducting hoses
Chemical resistance table hoses