



CARACAS EASY

Flexible, corrugated hose, for suction and delivery of a wide range of petroleum products on tank trucks. Available with EasyShell clamp system.

Hose construction

Tube: black, smooth, antistatic, synthetic rubber.

Reinforcement: high strength synthetic cord and steel helix wire.

Cover: green, corrugated (wrapped finish), synthetic rubber, oil, fuel, and weathering resistant.



Hardwall corrugated hose which is flexible and lightweight to be used on tank trucks for the suction and discharge of a wide range of petroleum products with up to 50% aromatic content.

Hose temperature range

-20°C to +70°C

Code	ID - mm	WP - bar	BP - bar	Weight - kg/m	BR - mm	Vacuum - bar	Lengtd - m
IH36538101	50	6	18	1,52	125	0,6	60
IH36538103	80	4	12	2,50	200	0,6	60
IH36538104	100	4	12	3,08	250	0,6	60

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5
 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses