



## CARBO G NW/L 10

Connection of household appliances to the gas line (NW/L) or to LPG bottles (NB/R).

### Hose constructon

**Tube:** Black, smooth NBR rubber compound, suitable for Domestic Gas

**Reinforcement:** Synthetic textile yarns

**Cover:** White (NW) or blue (NB), ageingresistant, smooth (/L) or ribbed (/R) SBR/EPDM rubber compound

### Temperature range

-20 °C (-4 °F) to +90 °C (+194 °F)



- Quarterly tested by IMQ (Italian Institute of Quality Approval)
- Low permeability
- Superior tensile strength
- White smooth cover for indoor and blue ribbed cover for outdoor
- Burst Pressure Value 3:1

**According to**  
UNI 7140

Number	I.D. mm	O.D. mm	WP bar	BP bar	Weight kg	Min R mm
IH30551600/100	13	20	10	30	0.29	51

## Contact us:

"DAIS GLOBAL " LTD  
3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria  
Telephone: +359 2 973 27 67  
Fax: +359 2 973 26 65  
E-mail: office@daisglobal.eu

## Catalogues:

Ducting hoses  
Industrial hoses  
Fittings  
Safety couplings  
Chemical resistance table ducting hoses  
Chemical resistance table hoses