



CARBOCORD EN 12115

Suitable for delivery of oil and fuel with an aromatic content not exceeding 50 %.

Hose construction

Tube: Black, smooth, NBR rubber compound, resistant to oil and fuel with an aromatic content not exceeding 50 %.

Reinforcement: Synthetic textile fabrics and built-in copper wires to provide electrical continuity between both ends.

Cover: Black, smooth, NBR/SBR rubber compound, antistatic ($R < 1 \text{ M/m}$), oil, fuel, abrasion, ageing and weather resistant.

Temperature range°

-25 °C ÷ +80 °C



- Meets TRbF 131 Teil 2 par 5.5 (-ame resistance)
- Optimal for tank truck application
- Electrical continuity guaranteed by copper wires if correctly assembled
- Burst Pressure Value 4:1

According to
EN 12115

Number	ID mm	OD mm	WP bar	BP bar	Weight kg	R мин mm
IH36522309/40	19	31	16	64	0,60	125
IH36522310/40	25	37	16	64	0,89	150
IH36522311/40	32	44	16	64	1,00	175
IH36522312/40	38	51	16	64	1,30	225
IH36522313/40	50	66	16	64	2,00	275
IH36522314/40	63,5	79	16	64	2,40	300
IH36522315/40	75	91	16	64	2,80	350
IH36522316/40	100	116	12	48	3,80	450

Contact us:

"DAIS GLOBAL " LTD
3, Poruchik Nedelcho Bonchev Str., fl. 5
1528 Sofia, Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
Industrial hoses
Fittings
Safety couplings
Chemical resistance table ducting hoses
Chemical resistance table hoses