



CARBOCORD EN ISO 7840 A1

Fire resistant fuel hose suitable for loading diesel, leaded and unleaded fuels with an aromatic content not exceeding 50 %, for small craft of - 24 m length of hull with permanently installed inboard engines. According to EN ISO 7840 type A1 permeability (4 g/m² hour). Complies with the essential requirements given in the European Directive for small craft 94/25/EC.

Hose construction

Tube: Black, smooth, antistatic (R < 1 M/m), oil and fuel resistant NBR rubber compound

Reinforcement: Synthetic textile yarns

Cover: Black, smooth, antistatic (R < 1 M/m), CR rubber compound resistant to abrasion, oil, fuel, weather and fire resistant.

Temperature Range

-40° to +100°C with peaks +120°C



- Type approval by RINA and Lloyd's Register
- Suitable for small craft according to European Directive 94/25/EC
- Fire resistant fuel hose
- Burst Pressure Value 8:1

Tolerances

according EN ISO 7840

I.D. ≤ 6 - 19 mm: ± 0,75
> 25 mm: ± 1,25

L ± 1%

Number	ID mm	OD mm	WP bar	BP bar	Weight kg	R min mm
IH36521204/40*	38	50	2.5	20	1.10	380
IH36521207/40*	50	62	2.5	20	1.40	500

Contact us:

"DAIS GLOBAL " LTD

3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria

Telephone: +359 2 973 27 67

Fax: +359 2 973 26 65

E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses

Industrial hoses

Fittings

Safety couplings

Chemical resistance table ducting hoses

Chemical resistance table hoses