



CARBOPRESS® D EN 1360/1

Designed for dispensing metered quantities of automotive fuels from dispensing equipment (petrol pumps). Resistant to leaded and unleaded petrol (gasoline) with an aromatic content not exceeding 50 %.

Hose construction

Tube: Black, smooth, NBR rubber compound, antistatic (R < 1 M/m)

Reinforcement: Synthetic textile yarns providing low dilation. Built-in copper wires to allow electrical continuity between fittings

Cover: Black, smooth, non-staining and antistatic (R < 1 M/m) CR rubber compound resistant to abrasion, oil, fuel and weathering.

Temperature range°

-25°C to +55°C



- Electrical continuity guaranteed by copper wires if correctly assembled
- Designed for petrol pumps
- Suitable for diesel and gasoline
- Burst Pressure Value 4:1

According to
EN 1360 Type 1

Number	ID mm	OD mm	WP bar	BP bar	Weight kg	R мин mm
IH30502403/80	15	25	16	48	0,45	75
IH30502420/50	16	26	16	48	0,47	80
IH30502420/90	16	26	16	48	0,47	80
IH30502421/80	18	30	16	48	0,64	90
IH30502407/50	19	31	16	48	0,63	95
IH30502411/50	21	31	16	48	0,53	105
IH36521140/40*	25	37	16	48	0,74	150

Contact us:

"DAIS GLOBAL " LTD
3, Poruchik Nedelcho Bonchev Str., fl. 5
1528 Sofia, Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
Industrial hoses
Fittings
Safety couplings
Chemical resistance table ducting hoses
Chemical resistance table hoses