



CARBOPRESS N/L 20

Suitable for fuel oils, petrol and diesel having an aromatic content not exceeded 50% and also for grease.

Hose construction

Tube: Black, smooth, NBR rubber compound

Reinforcement: Synthetic textile yarns

Cover: Black, smooth, abrasion, oil, fuel, and weather-resistant, antistatic ($R < 1 \text{ M/m}$) special NBR/EPDM rubber compound

Temperature range

-25 °C (-13 °F) to +80 °C (+176 °F) up to +100 °C (+212 °F) for fuels



- Dual pressure lines
- Also suitable for water and air in general service applications
- Burst Pressure Value 3:1

According to:
UNI EN ISO 1307

Number	ID mm	OD mm	WP bar	BP bar	Weight kg	R мин мм
IH30502001/100	6	14	20	60	0,17	50
IH30502002/100	8	17	20	60	0,24	65
IH30502003/100	10	19	20	60	0,27	80
IH30512006/100	13	23	20	60	0,38	105
IH30512010/80	16	26	20	60	0,44	130
IH30512007/80	19	30	20	60	0,57	150
IH30512009/50	25	36	20	60	0,71	200

Contact us:

"DAIS GLOBAL " LTD
3, Poruchik Nedelcho Bonchev Str., fl. 5
1528 Sofia, Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
Industrial hoses
Fittings
Safety couplings
Chemical resistance table ducting hoses
Chemical resistance table hoses