



## CARBOPRESS SAE J 30 R7

Low permeability, fire resistant hose, for lead and unleaded fuels in car and motorbike engines and gearbox lubricants where high performance and compliance to standards are important issue. Hose meets the American Standard SAE J30 R7.

### Hose construction

**Tube:** Black, smooth, antistatic ( $R < 1 \text{ M/m}$ ) NBR rubber compound, resistant to oils, fuels and unleaded petrol with aromatic content not exceeding 50 %

**Reinforcement:** Synthetic textile yarns

**Cover:** Black, smooth, antistatic ( $R < 1 \text{ M/m}$ ) CR rubber compound resistant to oils, abrasion, weather and fire.

### Temperature Range

-40°C ÷ +125°C

### Tolerances no

SAE J 30 R7



- Exceeds SAE J 30 R7 in WP
- Antistatic cover and tube compounds
- Suitable for B100 up to 70 °C
- Superior cover compound resistant to abrasion and weathering
- Burst Pressure Value 4:1

**According to**  
SAE J 30 R7

Number	ID mm	OD mm	WP bar	BP bar	Weight kg	R min mm
IH30872400/100	4	9.1	10	40	0.07	30
IH30872401/100	4.8	10.3	10	40	0.09	40
IH30872402/100	6.4	12.7	10	40	0.13	55
IH30872403/100	8	14.3	10	40	0.16	65
IH30872404/100	9.5	15.9	10	40	0.18	75
IH30872405/100	12.7	19.9	10	40	0.25	100

## Contact us:

"DAIS GLOBAL " LTD  
3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria  
Telephone: +359 2 973 27 67  
Fax: +359 2 973 26 65  
E-mail: office@daisglobal.eu

## Catalogues:

Ducting hoses  
Industrial hoses  
Fittings  
Safety couplings  
Chemical resistance table ducting hoses  
Chemical resistance table hoses