CEMENT SM 10

Suitable for suction and delivery of dry cement to road tankers and storage bins or silos.



- In-plant transfer/loading, bulk transport trucks
- Construction, general industry
- Good exibility
- Vacuum 0.8 bar
- Burst Pressure Value 3:1

Hose construction

Tube: Black, antistatic smooth abrasion resistant BR/NR rubber compound, abrasion max. 60 - 70 mm³
Reinforcement: Synthetic textile fabrics, embedded steel wire helix
Cover: Black, abrasion and weatherresistant, SBR rubber compound

Temperature range

-30 °C ÷ +70 °C

Tolerances

I.D. ± 1,59 mm
O.D. ± 2,38 mm
L ± 1%

According to

RMA steel mandrel

Number	I.D. mm	O.D. mm	WP bar	BP bar	Weight kg	Min R mm
CEMENT SM 10						
IH36923100/40	50	64	10	30	1,92	300
IH36923101/40	60	74	10	30	2,26	360
IH36923105/20	75	93	10	30	3,53	450
IH36923102/20	100	118	10	30	4,80	600
IH36923104/20	110	128	10	30	5,21	660
IH36923107/20	125	143	10	30	5,77	750
CEMENT SM H 10						
IH36923108/20	80	100	10	30	4,32	480
IH36923106/20	100	120	10	30	5,24	600
IH36923109/20	120	140	10	30	6,54	720

Contact us:
"DAIS GLOBAL " LTD
3,Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu

Catalogues:
Ducting hoses
Industrial hoses
Fittings
Safety couplings
Chemical resistance table ducting hoses
Chemical resistance table hoses