



## CP HiTex 480




Suction hose, especially suitable:

- for applications, where flame-retardant hoses are demanded
- for solids such as dust, powder and fibres
- for gaseous media such as vapors and smoke
- for de-dusting and suction plants, flue gas extraction, blast furnace exhaust and welding gas exhaust
- as bellows and compensator

### Hose construction

1. clamp profile supporting spiral: galvanised steel
2. wall: stainless steel wire reinforced and special coated glass fabric



### Temperature range

-60°C ÷ +400°C, with peaks up to +450°C



- very good heat resistance
- highly flexible + compressible 3:1
- abrasion predection via external clamp profile
- firm clamping of the wall in clamp profile
- small bending radius

No	I.D. mm	O.D. mm	Vacuum bar	Bend radius mm	Weight kg/m	Max length m
480-0038-0000	38	50	0,450	40	0,550	6
480-0040-0000	40	52	0,440	42	0,580	6
480-0050-0000	50	62	0,380	50	0,740	6
480-0055-0000	55	67	0,350	54	0,800	6
480-0060-0000	60	72	0,320	58	0,870	6
480-0065-0000	65	77	0,290	62	0,940	6
480-0070-0000	70	82	0,260	66	1,000	6
480-0075-0000	75	87	0,230	70	1,070	6
480-0080-0000	80	92	0,200	74	1,130	6
480-0090-0000	90	102	0,140	82	1,260	6
480-0100-0000	100	112	0,120	101	1,000	6
480-0110-0000	110	122	0,105	110	1,090	3 6
480-0115-0000	115	127	0,098	114	1,140	3 6
480-0120-0000	120	132	0,090	119	1,190	3 6
480-0125-0000	125	137	0,085	123	1,230	3 6
480-0130-0000	130	142	0,075	128	1,280	3 6
480-0140-0000	140	152	0,060	137	1,380	3 6
480-0150-0000	150	162	0,050	113	1,000	3 6

### Contact us:

"DAIS GLOBAL " LTD  
 3, Poruchik Nedelcho Bonchev Str., fl. 5  
 1528 Sofia, Bulgaria  
 Telephone: +359 2 973 27 67  
 Fax: +359 2 973 26 65  
 E-mail: office@daisglobal.eu

### Catalogues:

Ducting hoses  
 Industrial hoses  
 Fittings  
 Safety couplings  
 Chemical resistance table ducting hoses  
 Chemical resistance table hoses



No	I.D. mm	O.D. mm	Vacuum bar	Bend radius mm	Weight kg/m	Max length m
480-0160-0000	160	172	0,045	120	1,070	3 6
480-0170-0000	170	182	0,040	127	1,130	3 6
480-0175-0000	175	187	0,040	131	1,160	3 6
480-0180-0000	180	192	0,040	134	1,200	3 6
480-0200-0000	200	212	0,030	148	1,320	3 6
480-0215-0000	215	227	0,030	159	1,420	3 6
480-0225-0000	225	237	0,025	166	1,480	3 6
480-0250-0000	250	262	0,025	183	1,650	3 6
480-0275-0000	275	287	0,020	201	1,810	3 6
480-0300-0000	300	312	0,015	218	1,970	3 6
480-0315-0000	315	327	0,015	228	2,060	3 6
480-0325-0000	325	337	0,015	236	2,130	3 6
480-0350-0000	350	362	0,015	253	2,290	3 6
480-0375-0000	375	387	0,010	270	2,430	3 6
480-0400-0000	400	412	0,010	288	2,610	3 6
480-0450-0000	450	462	0,010	323	2,930	3 6
480-0500-0000	500	512	0,005	358	3,250	3 6
480-0600-0000	600	612	0,005	428	3,890	3
480-0700-0000	700	712	0,002	498	4,540	3
480-0750-0000	750	762	0,002	533	4,860	3
480-0800-0000	800	812	0,002	568	5,180	3
480-0900-0000	900	912	0,001	638	5,820	3
480-1000-0000	1000	1012	0,001	708	6,460	3

## Contact us:

"DAIS GLOBAL " LTD  
 3, Poruchik Nedelcho Bonchev Str., fl. 5  
 1528 Sofia, Bulgaria  
 Telephone: +359 2 973 27 67  
 Fax: +359 2 973 26 65  
 E-mail: office@daisglobal.eu

## Catalogues:

Ducting hoses  
 Industrial hoses  
 Fittings  
 Safety couplings  
 Chemical resistance table ducting hoses  
 Chemical resistance table hoses