




CP HiTex 487



- flexible hose/ ducting for hot and cold gases
- engine test bench, exhaust gas measurement
- high temperature extraction: oven, foundry, furnace, smelting, ceramics industry, glass industry, steel plant, aluminium mill
- bellows, compensator

Hose construction

- 1.clamp profile supporting spiral: galvanised steel
- 2.double-layer wall; wall: interior and exterior special-coated high-temperature fabric



- abrasion protection via external clamp profile
- secure clamping of the wall within the clamp profile
- highly flexible + compressible
- very good heat resistance
- conforms to RoHS guideline

Temperature range

-60°C ÷ +450°C, with peaks up to +600°C

No	I.D. inch / mm	O.D. mm	Pressure bar	Bending radius mm	Weight kg/m	Max length m
487-0075-0000	3 / 75-76	87	0,230	32,5	1,340	6
487-0080-0000	- / 80	92	0,200	34,0	1,420	6
487-0090-0000	3,5 / 89-90	102	0,140	37,0	1,580	6
487-0100-0000	4 / 100-102	112	0,120	51,0	1,290	6
487-0110-0000	- / 110	122	0,105	55,0	1,420	3 6
487-0115-0000	4,5 / 114-115	127	0,097	57,5	1,480	3 6
487-0120-0000	4,72 / 120	132	0,090	59,0	1,540	3 6
487-0125-0000	5 / 125-127	137	0,085	60,5	1,600	3 6
487-0130-0000	- / 130	142	0,075	63,0	1,660	-
487-0140-0000	5,5 / 140	152	0,060	67,0	1,780	3 6
487-0150-0000	6 / 150-152	162	0,050	38,0	1,340	3 6
487-0160-0000	6,3 / 160	172	0,045	40,0	1,460	3 6
487-0165-0000	6,5 / 165	177	0,045	41,0	1,500	-
487-0170-0000	- / 170	182	0,040	42,0	1,550	3 6
487-0175-0000	- / 175	187	0,040	43,5	1,590	-
487-0180-0000	7 / 178-180	192	0,040	44,0	1,630	3 6
487-0200-0000	8 / 200-203	212	0,030	48,0	1,810	3 6
487-0215-0000	- / 215	227	0,030	51,5	1,940	-
487-0225-0000	- / 225	237	0,025	53,5	2,030	3 6

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5
 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses



No	I.D. inch / mm	O.D. mm	Pressure bar	Bending radius mm	Weight kg/m	Max length m
487-0228-0000	9 / 228-229	240	0,025	54,0	2,110	-
487-0250-0000	- / 250	262	0,025	58,0	2,250	3 6
487-0254-0000	10 / 254	266	0,020	60,0	2,240	-
487-0275-0000	- / 275	287	0,020	63,5	2,470	-
487-0280-0000	11 / 280	292	0,015	65,0	2,510	-
487-0300-0000	- / 300	312	0,015	68,0	2,690	3 6
487-0305-0000	12 / 305	317	0,015	69,0	2,740	-
487-0315-0000	- / 315	327	0,015	70,5	2,820	-
487-0325-0000	- / 325	337	0,015	72,5	2,910	-
487-0330-0000	13 / 330	342	0,015	74,5	2,960	-
487-0350-0000	- / 350	362	0,015	78,0	3,130	3 6
487-0356-0000	14 / 356	368	0,015	79,5	3,180	-
487-0375-0000	- / 375	387	0,010	83,5	3,350	-
487-0400-0000	- / 400	412	0,010	88,0	3,560	3 6
487-0406-0000	16 / 405-406	418	0,010	89,5	3,610	-
487-0450-0000	- / 450	462	0,010	98,0	4,000	3 6
487-0457-0000	18 / 457	469	0,010	99,5	4,060	-
487-0500-0000	- / 500	512	0,005	108,0	4,440	3 6
487-0508-0000	20 / 508	520	0,005	110,0	4,510	-
487-0600-0000	- / 600	612	0,005	128,0	5,320	3
487-0610-0000	24 / 610	622	0,005	130,0	5,410	-
487-0700-0000	- / 700	712	0,002	148,0	6,200	3
487-0712-0000	28 / 712	724	0,002	150,5	6,310	-
487-0750-0000	- / 750	762	0,002	158,0	6,640	-
487-0800-0000	- / 800	812	0,002	168,0	7,070	3
487-0815-0000	32 / 813-815	827	0,001	171,5	7,200	-
487-0900-0000	- / 900	912	0,001	188,0	7,950	3
487-0915-0000	36 / 915	927	0,001	191,0	8,080	-
487-1000-0000	- / 1000	1012	0,001	208,0	8,830	3
487-1016-0000	40 / 1016	1028	0,001	213,0	8,970	-

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5
 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses