



CP HYP 450




Suction and blast hose, especially suitable:

- for solids such as dust, powder and fibres
- for gaseous media such as vapors and smoke
- for de-dusting and suction plants, flue gas extraction, blast furnace exhaust and welding gas exhaust
- for exhaust gas technique, engine construction, engine warming, aircraft construction and military construction
- as bellows and compensator

Hose construction

1. clamp profile supporting spiral: galvanised steel
2. wall: CSM coated polyester fabric



- vibration resistant
- very good heat resistance
- highly flexible + compressible 4:1
- abrasion predection via external clamp profile
- firm clamping of the wall in clamp profile

Temperature range

-40°C ÷ +170°C

No	I.D. mm	O.D. mm	Pressure bar	Vacuum bar	Bend radius mm	Weight kg/m	Max length m
450-0038-0000	38	50	0,805	0,450	40	0,570	6
450-0040-0000	40	52	0,785	0,440	42	0,590	6
450-0050-0000	50	62	0,700	0,380	50	0,760	6
450-0055-0000	55	67	0,660	0,350	54	0,820	6
450-0060-0000	60	72	0,630	0,320	58	0,890	6
450-0065-0000	65	77	0,600	0,290	62	0,960	6
450-0070-0000	70	82	0,570	0,260	66	1,030	6
450-0075-0000	75	87	0,545	0,230	70	1,100	6
450-0080-0000	80	92	0,525	0,200	74	1,160	6
450-0090-0000	90	102	0,485	0,140	82	1,300	6
450-0100-0000	100	112	0,320	0,120	78	1,030	6
450-0110-0000	110	122	0,300	0,105	85	1,130	3 6
450-0115-0000	115	127	0,290	0,098	89	1,170	3 6
450-0120-0000	120	132	0,280	0,090	92	1,220	3 6
450-0125-0000	125	137	0,275	0,085	96	1,270	3 6
450-0130-0000	130	142	0,270	0,075	99	1,320	3 6
450-0140-0000	140	152	0,255	0,060	106	1,420	3 6
450-0150-0000	150	162	0,175	0,050	113	1,040	3 6
450-0160-0000	160	172	0,165	0,045	120	1,110	3 6

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5
 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses



No	I.D. mm	O.D. mm	Pressure bar	Vacuum bar	Bend radius mm	Weight kg/m	Max length m
450-0170-0000	170	182	0,160	0,040	127	1,170	3 6
450-0175-0000	175	187	0,155	0,040	131	1,210	3 6
450-0180-0000	180	192	0,155	0,040	134	1,240	3 6
450-0200-0000	200	212	0,145	0,030	148	1,370	3 6
450-0215-0000	215	227	0,135	0,030	159	1,470	3 6
450-0225-0000	225	237	0,135	0,025	166	1,540	3 6
450-0250-0000	250	262	0,100	0,025	183	1,710	3 6
450-0275-0000	275	287	0,095	0,020	201	1,870	3 6
450-0300-0000	300	312	0,090	0,015	218	2,040	3 6
450-0315-0000	315	327	0,085	0,015	228	2,140	3 6
450-0325-0000	325	337	0,070	0,015	236	2,210	3 6
450-0350-0000	350	362	0,065	0,015	253	2,370	3 6
450-0375-0000	375	387	0,065	0,010	270	2,500	3 6

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5
 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses