



CP SIL 460




Suction and blast hose, especially suitable:

- for applications, where flame-retardant hoses are demanded
- for solids such as dust, powder and fibres
- for gaseous media such as vapors and smoke
- for de-dusting and suction plants, flue gas extraction, blast furnace exhaust and welding gas exhaust
- as bellows and compensator

Hose construction

1. clamp profile supporting spiral: all-stainless steel (INOX)
2. double-layer wall
wall: Silicon coated glass fabric



- very good heat resistance
- highly flexible + compressible 4:1
- abrasion predection via external clamp profile
- firm clamping of the wall in clamp profile
- small bending radius

Temperature range

-150°C ÷ +250°C, with peaks up to +270°C.

No	I.D. mm	O.D. mm	Pressure bar	Vacuum bar	Bend radius mm	Weight kg/m	Max length m
460-0050-0000	50	62	0,560	0,300	43	0,680	6
460-0055-0000	55	67	0,530	0,280	47	0,740	6
460-0060-0000	60	72	0,500	0,250	50	0,800	6
460-0065-0000	65	77	0,480	0,230	54	0,860	6
460-0070-0000	70	82	0,455	0,210	57	0,920	6
460-0075-0000	75	87	0,435	0,180	61	0,980	6
460-0080-0000	80	92	0,420	0,160	64	1,040	6
460-0090-0000	90	102	0,385	0,110	71	1,160	6
460-0100-0000	100	112	0,255	0,100	78	0,950	6
460-0110-0000	110	122	0,240	0,085	85	1,040	3 6
460-0115-0000	115	127	0,230	0,080	89	1,090	3 6
460-0120-0000	120	132	0,225	0,075	92	1,130	3 6
460-0125-0000	125	137	0,220	0,070	96	1,180	3 6
460-0130-0000	130	142	0,215	0,060	99	1,220	3 6
460-0140-0000	140	152	0,205	0,050	106	1,310	3 6
460-0150-0000	150	162	0,140	0,040	113	0,950	3 6
460-0160-0000	160	172	0,135	0,035	120	1,010	3 6
460-0170-0000	170	182	0,130	0,035	127	1,070	3 6
460-0175-0000	175	187	0,125	0,030	131	1,100	3 6

Contact us:

"DAIS GLOBAL " LTD
3, Poruchik Nedelcho Bonchev Str., fl. 5
1528 Sofia, Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
Industrial hoses
Fittings
Safety couplings
Chemical resistance table ducting hoses
Chemical resistance table hoses



No	I.D. mm	O.D. mm	Pressure bar	Vacuum bar	Bend radius mm	Weight kg/m	Max length m
460-0180-0000	180	192	0,125	0,030	134	1,130	3 6
460-0200-0000	200	212	0,115	0,025	148	1,250	3 6
460-0215-0000	215	227	0,110	0,020	159	1,340	3 6
460-0225-0000	225	237	0,105	0,020	166	1,400	3 6
460-0250-0000	250	262	0,080	0,020	183	1,560	3 6
460-0275-0000	275	287	0,075	0,015	201	1,710	3 6
460-0300-0000	300	312	0,070	0,010	218	1,860	3 6
460-0315-0000	315	327	0,065	0,010	228	1,950	3 6
460-0325-0000	325	337	0,060	0,010	236	2,030	3 6
460-0350-0000	350	362	0,050	0,010	253	2,160	3 6
460-0375-0000	375	387	0,050	0,010	270	2,260	3 6
460-0400-0000	400	412	0,045	0,010	288	2,470	3 6
460-0450-0000	450	462	0,045	0,005	323	2,770	3 6
460-0500-0000	500	512	0,030	0,005	358	3,070	3 6
460-0600-0000	600	612	0,025	0,005	428	3,680	3
460-0700-0000	700	712	0,020	0,002	498	4,290	3
460-0750-0000	750	762	0,020	0,001	533	4,600	3
460-0800-0000	800	812	0,020	0,001	568	4,900	3
460-0900-0000	900	912	0,015	0,001	638	5,500	3
460-1000-0000	1000	1012	0,015	0,001	708	6,110	3

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5
 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses