



DIVER-100 EN 250

Flexible hose for air supply in scuba diving systems. Designed to exceed the UNI EN 250 standard requirements (point 5,7) flexible hoses for medium pressure, related to tests on loose hoses (not assembled). Hose certified.

Hose construction

Tube: Black, smooth, heat and ageing resistant EPDM nitrosamine free rubber compound

Reinforcement: Synthetic textile yarns

Cover: Black, smooth EPDM nitrosamine free rubber compound, resistant to abrasion, sea water, heat and weathering

Temperature range

-30 °C ÷ +80 °C



- Tube compound vanilla avor
- Nitrosamine free compounds
- For assembly operation refer to the norm
- Burst Pressure Value 4:1

According to
EN 250

Number	I.D. mm	O.D. mm	WP bar	BP bar	Weight kg	R мин mm
IH30310133/100	6,3	12,3	35	120	0,12	60
IH30310126/100	7,3	13,7	35	120	0,15	75
IH30310124/80	8	14	35	120	0,14	80

Contact us:

"DAIS GLOBAL " LTD
3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
Telephone: +359 2 973 27 67
Fax: +359 2 973 26 65
E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
Industrial hoses
Fittings
Safety couplings
Chemical resistance table ducting hoses
Chemical resistance table hoses