



ELAFLEX EF D

As suction and discharge hose for barrels, containers, tank wagons and tankers. The steel helix ensures that the hose keeps in shape during suction and gravity operations.

Hose construction

Reinforcement: Two textile braids with tinned copper strands. Type EFS additionally with galvanised steel helix

Cover: Chloroprene (CR), black, smooth, electrically conducting. - Ozone resistant and flame proof.

Temperature range

-30°C ÷ +100°C Celsius, briefly up to 130° C (chemical resistance see overleaf). Steaming out for cleaning and sterilisation permissible up to +150° C, max. 30 minutes.



- Flexible
- Excellent chemical resistance
- FDA

According to

EN 12115 and German safety standard TRbF 131/2.

Number	I.D. mm	O.D. mm	WP bar	BP bar	Weight kg	R min mm
EFD13/40	13	22	16	25	0,4	100
EFD19/40	19	31	16	25	0,65	125
EFD25/40	25	37	16	25	0,9	150

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses