




EVA 373 EC



- flexible hose/ ducting for gases and for dust, powder, fibres
- industrial vacuum cleaners, vacuum cleaners
- explosion hazard area
- swimming pool cleaning
- scrubber, floor cleaning machine

Hose construction

- 1.self-supporting profile design
- 2.open profile geometry;
wall: EVA



- light weight
- highly flexible
- crush resistant
- floatable
- good resistance to alkalis and acids
- surface resistance $<10^6 \Omega$

Temperature range

-25 °C ÷ +65 °C;

No	I.D. inch / mm	O.D. mm	Pressure bar	Bending radius mm	Weight kg/m	Max length m
373-0020-1003	- / 20	26,5	0,500	44,5	0,085	-
373-0025-1003	1 / 25	32,2	0,500	53,5	0,150	30
373-0030-1003	- / 30	38,1	0,500	62,5	0,215	-
373-0032-1003	1,25 / 32	40,4	0,500	66,0	0,240	30
373-0038-1003	1,5 / 38	47,2	0,500	74,0	0,310	30
373-0040-1003	- / 40	49,4	0,500	80,0	0,320	30
373-0050-1003	2 / 50-51	60,4	0,500	97,0	0,440	30

Contact us:

"DAIS GLOBAL " LTD
 3, Poruchik Nedelcho Bonchev Str., fl. 5
 1528 Sofia, Bulgaria
 Telephone: +359 2 973 27 67
 Fax: +359 2 973 26 65
 E-mail: office@daisglobal.eu

Catalogues:

Ducting hoses
 Industrial hoses
 Fittings
 Safety couplings
 Chemical resistance table ducting hoses
 Chemical resistance table hoses