



## FUCINO 20

Suitable for a variety of industrial applications, where a flexible and lightweight discharge hose for water and non-aggressive liquids are required.

Specifically designed for irrigation equipment and submersible pumps.

### Hose construction

**Tube:** Black, smooth SBR nitrosamine free rubber compound

**Reinforcement:** Synthetic textile fabrics

**Cover:** Black, abrasion, ageing and weather-resistant SBR nitrosamine free rubber compound



- Can be rolled at for easy transport and storage
- Resistant to Ozone and weathering
- Available in two different pressure rates
- Nitrosamine free
- Burst Pressure Value 3:1

### Temperature range

-30 °C ÷ +80 °C

### According to

RMA steel mandrel

Number	I.D. mm	O.D. mm	WP bar	BP bar	Weight kg	Min R mm
IH36203276/40	50	58	20	60	0,94	-
IH36203278/40	60	68	20	60	1,10	-
IH36203279/20	75	86	20	60	1,92	-
IH36203280/20	80	91	20	60	2,05	-
IH36203281/20	90	103,5	20	60	2,68	-
IH36203282/20	100	113	20	60	2,97	-
IH36203283/20	120	133	20	60	3,52	-

### Contact us:

"DAIS GLOBAL " LTD  
 3, Poruchik Nedelcho Bonchev Str., fl. 5, 1528 Sofia, Bulgaria  
 Telephone: +359 2 973 27 67  
 Fax: +359 2 973 26 65  
 E-mail: office@daisglobal.eu

### Catalogues:

Ducting hoses  
 Industrial hoses  
 Fittings  
 Safety couplings  
 Chemical resistance table ducting hoses  
 Chemical resistance table hoses